

## Uni-Gates

Manufacturer: Jacksons Fencing.  
Web: [www.jacksons-fencing.co.uk](http://www.jacksons-fencing.co.uk).  
Tel: +44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Uni-gates.

•Type:

-Narrow Uni-Gate:

[Not required].

[255000]. - 900 mm long x 1270mm high, with single brace.

[255090]. - 1050 mm long x 1270mm high, with single brace.

[251100]. - 1200 mm long x 1270mm high.

[255200]. - 1500 mm long x 1270mm high.

[255300]. - 1800 mm long x 1270mm high.

[255400]. - 2100 mm long x 1270mm high.

-Wide Uni-Gate:

[Not required].

[255500]. - 2400 mm long x 1270mm high

[256600]. - 2700 mm long x 1270mm high.

[257700]. - 3000 mm long x 1270mm high.

[258800]. - 3300 mm long x 1270mm high.

[259900]. - 3600 mm long x 1270mm high.

[256000]. - 3900 mm long x 1270mm high.

[256100]. - 4200 mm long x 1270mm high.

•Fixing kit for single or double leaf gates TRHSSL/TRHSDL: hinges, latch and posts:

[Required].

[Not required].

### Options

Type:

- 900–4200 mm wide.
- Height: 1270 mm.

### Fixing kit TRHSSL:

Includes galvanized fittings, hinge set, spring catch fitted, anti-lift device, padlock 2100 mm, 175 x 175 mm hanging post and 150 x 150 mm shutting post.

### TRHSDL:

Includes galvanized fittings, hinge set, Loop over catch fitted, anti-lift device, padlock 2100 mm, 175 x 175 mm hanging and shutting post.

### Features:

- Designed with heavy top rail over entire width for extra strength.
- Both hanging and slam stiles are drilled to allow gates to be hung on the left or right.
- Planed finish.
- Rail and brace crossings are bolted with stainless steel bolts.

## Jacksons Fencing

### NBS Specification

- Top bars are chamfered.
- Cross braced for extra strength.
- All joints are mortised and tenoned or dowelled..
- Commonly used as driveway gates or field gates.
- Supplied in natural Jakcured finish.
- All timber used through out is superior quality and guaranteed for twenty five years.

### **Installation**

In accordance to manufacturers instructions